

en:gate®



TECHNICAL DATA SHEET
LED DOWNLIGHT ICEBERG

LED DOWNLIGHT ICEBERG

LED DOWNLIGHT ICEBERG is delivered with optimized optics, providing accurate light distribution and high efficiency light output. LED DOWNLIGHT ICEBERG available in 2 light distribution patterns to enable the suitability for any interior decoration.

LED DOWNLIGHT ICEBERG enables the fixture to be pulled out at 40° and rotate at 355°. It has a flexible design where it can be used as downlight and spotlight for any application. LED DOWNLIGHT ICEBERG is suitable for applications mainly in hotel lobby, restaurants and shopping malls.

HIGHLIGHTS

- Easy installation
- Up to 80% reduction in power consumption¹
- Average rated lifespan of 25,000 hours
- 100,000 times of switching cycle
- Energy efficiency class: A
- Low maintenance costs by reducing re-lamp frequency
- Environmental friendly – free of mercury and hazardous materials
- Starting time < 0.5 seconds
- Instant start < 1 second

FEATURES

- Colors available: black & white
- CRI: 80
- Will not fade colors, avoids inventory spoilage
- Operating temperature: -20°C - +40°C
- Lumen maintenance factor: L70
- Weight: 0.95 kg
- IP Rating: IP20
- Low heat generation, short amortization period
- Warranty: 5 years luminaire, 3 years driver²

APPLICATION

- Hotel lobby, restaurants, shopping malls



For further information scan the QR Code or visit www.en-gate.com/ICEBERG

TECHNICAL DETAILS

LED DOWNLIGHT ICEBERG

Power Max.	Replace Incandescent	CCT	Light Output Min.	Lux @ 1 m (typ.)	CRI	Beam Angle	Voltage	Color	Power factor	Art.-No.
30W	70W	3.000K	2.350lm	9.100lx	80	25°	100-240V	□	0.9	T2-ICE-LJ-85BX6T
30W	70W	4.000K	2.350lm	9.100lx	80	25°	100-240V	□	0.9	T2-ICE-LJ-85B06T
30W	70W	5.700K	2.350lm	9.100lx	80	25°	100-240V	□	0.9	T2-ICE-LJ-85BF6T
30W	70W	3.000K	2.350lm	6.500lx	80	38°	100-240V	□	0.9	T2-ICE-MJ-85BX6T
30W	70W	4.000K	2.350lm	6.500lx	80	38°	100-240V	□	0.9	T2-ICE-MJ-85B06T
30W	70W	5.700K	2.350lm	6.500lx	80	38°	100-240V	□	0.9	T2-ICE-MJ-85BF6T
30W	70W	3.000K	2.350lm	9.100lx	80	25°	100-240V	■	0.9	T2-ICE-LJ-85AX6T
30W	70W	4.000K	2.350lm	9.100lx	80	25°	100-240V	■	0.9	T2-ICE-LJ-85A06T
30W	70W	5.700K	2.350lm	9.100lx	80	25°	100-240V	■	0.9	T2-ICE-LJ-85AF6T
30W	70W	3.000K	2.350lm	6.500lx	80	38°	100-240V	■	0.9	T2-ICE-MJ-85AX6T
30W	70W	4.000K	2.350lm	6.500lx	80	38°	100-240V	■	0.9	T2-ICE-MJ-85A06T
30W	70W	5.700K	2.350lm	6.500lx	80	38°	100-240V	■	0.9	T2-ICE-MJ-85AF6T

□ White ■ Black

