

en:gate®



TECHNICAL DATA SHEET LED TRACKLIGHT SMART

LED TRACKLIGHT SMART

The LED TRACKLIGHT SMART can be applied to any homes, retails and commercial area.

The Chip on Board (COB) improves the performance of the lighting as it is a cheaper solution compared to the traditional LED lighting. Furthermore, with the stylish and practical design, the LED TRACKLIGHT SMART can be mounted to ceiling and walls for a decorative wall display light.

HIGHLIGHTS

- Easy installation
- Up to 80% reduction in power consumption¹
- Average rated lifespan of 25,000 hours
- 100,000 times of switching cycle
- Energy efficiency class: A
- Low maintenance costs by reducing re-lamp frequency
- Environmental friendly – free of mercury and hazardous materials
- Starting time < 0.5 seconds
- Instant start < 1 second

FEATURES

- Available in 2 colors: Black & White
- Superior color rendering with 80 & 90 CRI
- Will not fade colors, avoids inventory spoilage
- Operating temperature: -20°C - +40°C
- Lumen maintenance factor: L70
- Weight: 1.1 kg
- IP Rating: IP20
- Low heat generation, short amortization period
- CE and RoHS certified
- Warranty: 5 years luminaire, 3 years driver²

APPLICATION

- Commercial, industry, homes



For further information scan the QR Code or visit www.en-gate.com/SMART

TECHNICAL DETAILS

LED TRACKLIGHT SMART

Power Max.	Replace	CCT	Light Output Min.	CRI	Beam Angle	Field Angle	Body Color	Voltage	Power factor	Art.-No.
Incandescent										
45W	70W	3.000K	3.500lm	80	25°	60°	■	100-240V	0.95	T2-SMA-2U-81AP6T
45W	70W	4.000K	3.500lm	80	25°	60°	■	100-240V	0.95	T2-SMA-2U-81A26T
45W	70W	6.000K	3.500lm	80	25°	60°	■	100-240V	0.95	T2-SMA-2U-81AG6T
45W	70W	3.000K	3.500lm	80	45°	80°	■	100-240V	0.95	T2-SMA-2U-81AZ6T
45W	70W	4.000K	3.500lm	80	45°	80°	■	100-240V	0.95	T2-SMA-2U-81A66T
45W	70W	6.000K	3.500lm	80	45°	80°	■	100-240V	0.95	T2-SMA-2U-81AH6T
45W	70W	3.000K	3.500lm	80	25°	60°	□	100-240V	0.95	T2-SMA-2U-81BP6T
45W	70W	4.000K	3.500lm	80	25°	60°	□	100-240V	0.95	T2-SMA-2U-81B26T
45W	70W	6.000K	3.500lm	80	25°	60°	□	100-240V	0.95	T2-SMA-2U-81BG6T
45W	70W	3.000K	3.500lm	80	45°	80°	□	100-240V	0.95	T2-SMA-2U-81B26T
45W	70W	4.000K	3.500lm	80	45°	80°	□	100-240V	0.95	T2-SMA-2U-81B66T
45W	70W	6.000K	3.500lm	80	45°	80°	□	100-240V	0.95	T2-SMA-2U-81BH6T
45W	70W	3.000K	3.000lm	90	25°	60°	■	100-240V	0.95	T2-SMA-2U-81AP7T
45W	70W	4.000K	3.000lm	90	25°	60°	■	100-240V	0.95	T2-SMA-2U-81A27T
45W	70W	6.000K	3.000lm	90	25°	60°	■	100-240V	0.95	T2-SMA-2U-81AG7T
45W	70W	3.000K	3.000lm	90	45°	80°	■	100-240V	0.95	T2-SMA-2U-81AZ7T
45W	70W	4.000K	3.000lm	90	45°	80°	■	100-240V	0.95	T2-SMA-2U-81A67T
45W	70W	6.000K	3.000lm	90	45°	80°	■	100-240V	0.95	T2-SMA-2U-81AH7T
45W	70W	3.000K	3.000lm	90	25°	60°	□	100-240V	0.95	T2-SMA-2U-81BP7T
45W	70W	4.000K	3.000lm	90	25°	60°	□	100-240V	0.95	T2-SMA-2U-81B27T
45W	70W	6.000K	3.000lm	90	25°	60°	□	100-240V	0.95	T2-SMA-2U-81BG7T
45W	70W	3.000K	3.000lm	90	45°	80°	□	100-240V	0.95	T2-SMA-2U-81B27T
45W	70W	4.000K	3.000lm	90	45°	80°	□	100-240V	0.95	T2-SMA-2U-81B67T
45W	70W	6.000K	3.000lm	90	45°	80°	□	100-240V	0.95	T2-SMA-2U-81BH7T

■ black □ white

