

en:gate®



TECHNICAL DATA SHEET
LED TRACKLIGHT SMART MINI

LED TRACKLIGHT SMART MINI

The LED TRACKLIGHT SMART MINI is the smaller version of existing LED TRACKLIGHT SMART.

It can be smaller in size, it is still powerful compared to the traditional LED lighting. LED TRACKLIGHT SMART MINI can be applied to any homes, restaurants and hotels.

HIGHLIGHTS

- Easy installation
- Up to 80% reduction in power consumption¹
- Average rated lifespan of 25,000 hours
- 100,000 times of switching cycle
- Energy efficiency class: A
- Low maintenance costs by reducing re-lamp frequency
- Environmental friendly – free of mercury and hazardous materials
- Starting time < 0.5 seconds
- Instant start < 1 second

FEATURES

- Colors available: black & white
- Superior color rendering with 80 CRI
- Will not fade colors, avoids inventory spoilage
- Operating temperature: -20°C - +40°C
- Lumen maintenance factor: L70
- Weight: 1.25 kg
- IP Rating: IP20
- Low heat generation, short amortization period
- Warranty: 5 years luminaire, 3 years driver²

APPLICATION

- Homes, restaurants and hotels



For further information scan the QR Code or visit www.en-gate.com/SMART_MINI

TECHNICAL DETAILS

LED TRACKLIGHT SMART MINI

Power	Replace	CCT	Light Output	Lux @ 1 m	CRI	Beam Angle	Body Color	Voltage	Power	Art.-No.
Max.	Incandescent		Min.	(typ.)					factor	
30W	70W	3.000K	2.350lm	9.400lx	80	15°	□	100-240V	0.9	T2-SMM-KS-82BX6T
30W	70W	4.000K	2.350lm	9.400lx	80	15°	□	100-240V	0.9	T2-SMM-KS-82B06T
30W	70W	5.700K	2.350lm	9.400lx	80	15°	□	100-240V	0.9	T2-SMM-KS-82BF6T
30W	70W	3.000K	2.350lm	9.400lx	80	25°	□	100-240V	0.9	T2-SMM-LS-82BX6T
30W	70W	4.000K	2.350lm	9.400lx	80	25°	□	100-240V	0.9	T2-SMM-LS-82B06T
30W	70W	5.700K	2.350lm	9.400lx	80	25°	□	100-240V	0.9	T2-SMM-LS-82BF6T
30W	70W	3.000K	2.350lm	9.400lx	80	15°	■	100-240V	0.9	T2-SMM-KS-82AX6T
30W	70W	4.000K	2.350lm	9.400lx	80	15°	■	100-240V	0.9	T2-SMM-KS-82A06T
30W	70W	5.700K	2.350lm	9.400lx	80	15°	■	100-240V	0.9	T2-SMM-KS-82AF6T
30W	70W	3.000K	2.350lm	9.400lx	80	25°	■	100-240V	0.9	T2-SMM-LS-82AX6T
30W	70W	4.000K	2.350lm	9.400lx	80	25°	■	100-240V	0.9	T2-SMM-LS-82A06T
30W	70W	5.700K	2.350lm	9.400lx	80	25°	■	100-240V	0.9	T2-SMM-LS-82AF6T
30W	70W	3.000K	1.180lm	9.400lx	90	15°	□	100-240V	0.9	T2-SMM-KS-82BX7T
30W	70W	4.000K	1.180lm	9.400lx	90	15°	□	100-240V	0.9	T2-SMM-KS-82B07T
30W	70W	5.700K	1.180lm	9.400lx	90	15°	□	100-240V	0.9	T2-SMM-KS-82BF7T
30W	70W	3.000K	1.180lm	9.400lx	90	25°	□	100-240V	0.9	T2-SMM-LS-82BX7T
30W	70W	4.000K	1.180lm	9.400lx	90	25°	□	100-240V	0.9	T2-SMM-LS-82B07T
30W	70W	5.700K	1.180lm	9.400lx	90	25°	□	100-240V	0.9	T2-SMM-LS-82BF7T
30W	70W	3.000K	1.180lm	9.400lx	90	15°	■	100-240V	0.9	T2-SMM-KS-82AX7T
30W	70W	4.000K	1.180lm	9.400lx	90	15°	■	100-240V	0.9	T2-SMM-KS-82A07T
30W	70W	5.700K	1.180lm	9.400lx	90	15°	■	100-240V	0.9	T2-SMM-KS-82AF7T
30W	70W	3.000K	1.180lm	9.400lx	90	25°	■	100-240V	0.9	T2-SMM-LS-82AX7T
30W	70W	4.000K	1.180lm	9.400lx	90	25°	■	100-240V	0.9	T2-SMM-LS-82A07T
30W	70W	5.700K	1.180lm	9.400lx	90	25°	■	100-240V	0.9	T2-SMM-LS-82AF7T

□ White ■ Black

